

// FAAP – L-SHAPED EDGING PROFILES ALUMINUM COLOR COATED

Item-no.	FAAP
Product group	Tile trim
Height	6* / 8 / 10 / 11** / 12,5 mm (*only in white, bahamabeige, black, silver grey / **only in white)
Length	250 / 270** cm
Material	Aluminum 6060 in accordance to DIN EN 755-1 (extruded Aluminum) AlMgSi0.5
Surface	BW: white - RAL 9003 BG: bahamabeige SGL: black glossy - RAL 9005 SW: black matt - RAL 9005 SG: silver grey (light grey) - RAL 7035 CA: caramel AG: ash grey MHG: manhattan grey
Color coating in accordance to GSB	> 60 µm
Fire resistance in accordance to DIN EN 13501	A1 (non-flammable)
Linear coefficient of expansion	24 x 10 ⁻⁶ m/m°C
Density approx	2.7 - 2.8 kg/dm ³
Hardness approx	70 - 80 HB
Chemical resistance	approx. 4.5 - 8.5 pH
Melting point at	approx. 660°C
Other Properties	Production in accordance to DIN EN 120-1 Aluminum and Aluminum alloys – Technical delivery terms. Factory production controls in accordance to DIN 18200.
Drawing	