

// FVAE / FVGS / FVGT - ROUND EDGE PROFILES CLOSED ALUMINUM

Item-no.	FVAE / FVGS / FVGT - matt
Product group	Tile trim
Height	6* / 8** / 10 / 12.5 mm (*only FVGS / **only FVGS, FVGT)
Length	250 / 300* cm
Thickness	approx. 1.5 mm
Material	Aluminum 6060 in accordance to DIN EN 755-1 (extruded Aluminum) AlMgSi0,5
Surface	FVGS: silver anodized FVGT: titanium anodized FVAE-M: brass anodized FVAE-BS: bronze anodized brushed
Properties	Surface anodised in accordance to DIN 17611
Fire resistance in accordance to DIN EN 13501	A1 (non-flammable)
Linear coefficient of expansion	$24 \times 10^{-6} \text{ m/m}^\circ\text{C}$
Density approx	2.7 - 2.8 kg/dm <sup>3</sup>
Hardness approx	70 - 80 HB
Chemical resistance	approx. 4.5 - 8.5 pH
Melting point at	approx. 660°C
Other Properties	Production in accordance to DIN EN 120-1 Aluminum and Aluminum alloys - Technical delivery terms. Factory production controls in accordance to DIN 18200.
Drawing	