

**fuma // CLASSIC – L-SHAPED EDGING PROFILES**  
Aluminum

<b>Item-no.</b>	FAA
<b>Product group</b>	Tile trim
<b>Height</b>	2* / 3* / 4.5*/** / 6** / 8** / 9 / 10** / 11** / 12.5** / 15 / 16.5 / 18.5 / 20 / 22 / 25 / 30 / 40 mm
<b>Length</b>	250 / 270 / 300 cm (*only available in 250 cm / **only available in 270 cm)
<b>Thickness</b>	approx. 1.5 mm
<b>Material</b>	Aluminum 6060 in accordance to DIN EN 755-1 (extruded Aluminum) AlMgSi0,5
<b>Surface</b>	natural
<b>Natural oxide coating</b>	0.1 µm approx.
<b>Fire resistance in accordance to DIN EN 13501</b>	A1 (non-flammable)
<b>Linear coefficient of expansion</b>	24 x 10 <sup>-6</sup> m/m°C
<b>Density approx</b>	2.7 - 2.8 kg/dm <sup>3</sup>
<b>Hardness approx</b>	70 - 80 HB
<b>Chemical resistance</b>	high
<b>Melting point at</b>	approx. 660°C
<b>Other Properties</b>	Production in accordance to DIN EN 120-1 Aluminum and Aluminum alloys – Technical delivery terms. Factory production controls in accordance to DIN 18200.

<b>Drawing</b>	
----------------	---------------------------------------------------------------------------------------