

**fuma // CLASSIC - L-SHAPED EDGING PROFILES**  
 Aluminum color coated

<b>Item-no.</b>	FAAP
<b>Product group</b>	Tile trim
<b>Height</b>	6* / 8 / 10 / 11** / 12,5 mm (*only in white, bahamabeige, black, silver grey / **only in white, black, black matt)
<b>Length</b>	250 / 270** cm
<b>Material</b>	Aluminum 6060 in accordance to DIN EN 755-1 (extruded Aluminum) AlMgSi0.5
<b>Surface</b>	BW: white - RAL 9003 BG: bahamabeige SGL: black - RAL 9005 SW: black matt - RAL 9005 SG: silver grey (light grey) - RAL 7035 CA: caramel AG: ash grey MHG: manhattan grey
<b>Color coating in accordance to GSB</b>	> 60 µm
<b>Fire resistance in accordance to DIN EN 13501</b>	A1 (non-flammable)
<b>Linear coefficient of expansion</b>	$24 \times 10^{-6} \text{ m/m}^\circ\text{C}$
<b>Density approx</b>	2.7 - 2.8 kg/dm <sup>3</sup>
<b>Hardness approx</b>	70 - 80 HB
<b>Chemical resistance</b>	approx. 4.5 - 8.5 pH
<b>Melting point at</b>	approx. 660 °C
<b>Other Properties</b>	Production in accordance to DIN EN 120-1 Aluminum and Aluminum alloys - Technical delivery terms. Factory production controls in accordance to DIN 18200.
<b>Drawing</b>	