

fuma // CLASSIC – L-SHAPED EDGING PROFILES
 Aluminum texture coated

Item-no.	FAAP	
Product group	Tile trim	
Height	8 / 10 / 11* / 12.5 mm (*available in grey metallic, anthracite, terra brown, umbra, sand, quarz, dolomitic)	
Length	250 cm	
Material	Aluminum 6060 in accordance to DIN EN 755-1 (extruded Aluminum) AlMgSi0.5	
Surface	GM: grey metallic AT: anthracite TB: terra brown UB: umbra SD: sand QZ: quarz DL: dolomitic ARC: arctic	KRD: chalk CR: creme MSW: black SWB: black brilliant ATB: anthracite brilliant SGB: silver grey brilliant BGB: beige brilliant WB: white brilliant
Powder coating in accordance to GSB	> 60 µm	
Fire resistance in accordance to DIN EN 13501	A1 (non-flammable)	
Linear coefficient of expansion	24 x 10 ⁻⁶ m/m°C	
Density approx	2.7 - 2.8 kg/dm ³	
Hardness approx	70 - 80 HB	
Chemical resistance	approx. 4.5 - 8.5 pH	
Melting point at	approx. 660°C	
Other Properties	Production in accordance to DIN EN 120-1 Aluminum and Aluminum alloys – Technical delivery terms. Factory production controls in accordance to DIN 18200.	
Drawing		