

**fuma // MOVE - THICK-BED PROFILES**  
 Hard-soft PVC

<b>Item-no.</b>	ED
<b>Product group</b>	Expansion Joint Profil
<b>Height</b>	30 <sup>**</sup> / 40 / 50 / 65* mm (*not available in dark grey / **only available in grey)
<b>Length</b>	250 cm
<b>Visible width</b>	8 mm
<b>Material</b>	Side parts made from PVC-U (= polyvinyl chloride-hard) Infill is made from elastic PVC-P (= polyvinyl chloride-soft)
<b>Surface</b>	HG: grey SW: black DG: dark grey BG: beige
<b>Properties</b>	Coextrusion
<b>Fire resistance in accordance to DIN 4102-T1</b>	B1 (difficult-flammable)
<b>Load bearing</b>	15 N/mm <sup>2</sup> (for dynamical point load) for medium-heavy loading areas
<b>Hardness</b>	Shore A 65 +/-5
<b>Temperature resistance</b>	up to approx. 65°C, shortly approx. + 90° C
<b>Chemical resistance</b>	In general constant in regard to salt solutions, concentrative acids and bases, chlorine and ozone and good resistance to light and weathering
<b>Other properties</b>	Factory production controls in accordance to DIN 18200.
<b>Drawing</b>	